

AC1900 Wi-Fi Router

Dual Band | MU-MIMO







1300 Mbps 5 GHz + 600 Mbps 2.4 GHz[†]



Highlights

Speeds up to 1900 Mbps

1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz are ideal for both everyday tasks and lag-free online entertainment.⁺

Smart Connect

Smart Connect unites 2.4 GHz and 5 GHz band into a single Wi-Fi SSID and helps the router automatically switch each device's connection to the best available Wi-Fi band.



SSID 1 **2.4 GHz**



Highlights

Vast Wi-Fi Coverage

Four external omni-directional antennas create strong, clear, dependable Wi-Fi throughout your home. Beamforming detects the location of your connected devices and concentrates the Archer C80's signal towards them to optimize wireless connections.[†]



efficient.‡







Regular Router

MU-MIMO technology serves multiple devices at once, reducing wait time, increasing Wi-Fi throughput for every device, and making each stream more

Highlights

Airtime Fairness

Equally divides network time between new devices, such as your gaming rig and older devices to improve your overall Wi-Fi performance and reliability.

Easy Setup and Use

your smartphone.





Scan the QR code to download TP-Link Tether.

Installation is simple, thanks to an intuitive web interface and the powerful TP-Link app, Tether. Tether lets you manage your network settings with



TP-Link AC1900 Wi-Fi Router Archer C80

Features



Speed

- 802.11ac Technology Powered by 802.11ac Wi-Fi technology, Archer C80 creates a reliable, blazing-fast network.
- Ultimate Wireless Speed 1300 Mbps on 5 GHz + 600 Mbps on 2.4 GHz
- Gigabit Internet Access Take full advantages of broadband speeds up to 1 Gbps



Wi-Fi Range

- Ultimate Range Wi-Fi Four external antennas deliver a Wi-Fi signal to every corner of your home, making all of your connections more efficient and stable
- Beamforming Technology Concentrates Wi-Fi signals
 towards individual devices to ensure stronger connections



Reliability

- Airtime Fairness Balances airtime usage of connected devices to improve overall throughput and efficiency
- Smart Connect Intelligently switches each device's connection to the optimum available Wi-Fi band
- Vxworks System Utilizes the real-time Vxworks system, which has pre-assigned RAM strategy to provide more stable and high-responsive experience.

Features



Easy Management

- Intuitive Web UI Ensures quick and simple Installation without hassle
- Hassle-free Management with Tether App Network management is made easy with the TP-Link Tether App, available on any Android and iOS device
- TP-Link ID Binds the router to your TP-Link ID and other family member's accounts to manage the router



Security

- Encryptions for Secure Network WPA-PSK and WPA2-PSK
 Wi-Fi Sharing Easily shares your Wi-Fi access with a QR code
 encryptions provide active protection against security threats
- Wi-Fi Schedule The wireless network can be automatically off
 Guest Network Keeps your main network secure by creating a separate network for friends and visitors
 Wi-Fi Schedule The wireless network can be automatically off
 Wi-Fi Schedule The wireless network can be automatically off
 Wi-Fi Schedule The wireless network can be automatically off
 Wi-Fi Schedule The wireless network can be automatically off
 Wi-Fi Schedule The wireless network can be automatically off
- Parental Controls Restricts internet access time and contents
 for children devices
 LED Control Automatically turns your router's LEDs off within
 a specified period

Ease of Use

Specifications

Hardware

- Ethernet Ports: 1× 10/100/1000 Mbps WAN Port, 4×10/100/1000 Mbps LAN Port
- Buttons: WPS/Wi-Fi Button, Power On/Off Button, Reset Button
- Antennas: 4 Fixed Omni Directional Antennas
- External Power Supply: US version 12V/1.5A

EU version 12V/1A

• Dimensions (W x D x H): $8.5 \times 4.6 \times 1.26$ in ($215 \times 117 \times 32$ mm)



Wireless

- Frequency: 2.4 GHz and 5 GHz
- Transmit Power:
- FCC:<30dBm(2.4 GHz & 5 GHz)
- Reception Sensitivity: 5 GHz:
- 11a 6Mbps:-98dBm, 11a 54Mbps:-78dBm 2.4 GHz:
- 11g 6Mbps:-97dBm, 11a 54Mbps:-77dBm

• Wireless: 1300 Mbps on 5 GHz + 600 Mbps on 2.4 GHz

CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz)

11ac VHT20_MCS0:-98dBm, 11ac VHT20_MCS8:-72dBm 11ac VHT40_MCS0:-92dBm, 11ac VHT40_MCS9:-68dBm 11ac VHT80_MCS0:-89dBm, 11ac VHT80_MCS9:-64dBm

11n VHT20_MCS0:-97dBm, 11n VHT20_MCS8:-72dBm 11n VHT40_MCS0:-92dBm, 11n VHT40_MCS9:-67dBm • Wireless Function: Enable/Disable Wireless Radio, WMM · Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

Specifications

Software

- Quality of Service: Device Prioritization
- · WAN Type: Dynamic IP/Static IP/PPPoE(Dual Access)/PPTP(Dual Access)/L2TP(Dual Access)
- · Management: Access Control, Local Management, Remote Management
- DHCP: Server, DHCP Client List, Address Reservation
- Port Forwarding: Port Forwarding, Port Triggering, UPnP, DMZ
- · Dynamic DNS: DynDns, NO-IP, TP-Link
- Access Control: Parental Controls, Local Management Control, White List, Black List
- Firewall Security: SPI Firewall, IP and MAC Address Binding
- · Protocols: IPv4, IPv6
- Guest Network: 2.4 GHz Guest Network, 5 GHz Guest Network

Others

- · Certification:
- CE, FCC, RoHS
- System Requirements: NetWare, UNIX or Linux
- Java-enabled browser
- Cable or DSL Modem
- Environment:

- Package Contents
- Wireless Router Archer C80
- Power Adapter
- **RJ45 Ethernet Cable**
- Quick Installation Guide



For more information, please visit

https://www.tp-link.com/products/details/?model=Archer+C80_V1

or scan the QR code left

Attention: This device may only be used indoors in all EU member states and EFTA countries.

Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders.

Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

‡Use of MU-MIMO requires clients to also support MU-MIMO. ©2020 TP-Link

Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS,

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other

Subscription with an internet service provider (for internet access)

Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing