

## DS-K1T341AM-S Face Recognition Terminal



- Face recognition distance: 0.3 m to 1.5 m
- 1500 face capacity, 1,500 card capacity and 150,000 event capacity
- Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
- Two-way audio with indoor station and master station
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Configuration via the web client
- Remotely opens door and starts live view via Hik-Connect
- Supports ISAPI and EHome 5.0 protocols

## ▪ Specification

<b>Display</b>	
Dimensions	4.3-inch
Type	LCD
Operation method	Capacitive touch screen
<b>Video</b>	
FOV	HFOV = 41.5°; VFOV = 75.5°; DFOV = 87°
Pixel	2 MP (video stream: 720P)
Lens	× 2
<b>Audio</b>	
Tone quality	Noise suppression and echo cancellation
<b>Network</b>	
Wired network	10 M/100 M/1000 M self-adaptive
<b>Interface</b>	
Network interface	1
Lock output	1
Exit button	1
Door contact input	1
Power interface	2-pin
<b>Authentication</b>	
Card type	Mifare 1 card
Card reading frequency	13.56MHz
<b>Function</b>	
QR code recognition	Support
Face anti-spoofing	Support
Audio prompt	Support
Time synchronization	Support
<b>General</b>	
button	Touch Screen
Power supply method	2 pin connecter
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	0 to 90% (No condensing)
Dimensions	172.5 mm × 83.2 mm × 22.7 mm (6.79" × 3.27" × 0.89")
Application environment	Indoor and outdoor
Installation	Surface mounting

## ▪ Available Model

DS-K1T341AM-S

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

