Datasheet



Tapo Smart Temperature & Humidity Monitor

Tapo T315



Clear & Sharp E-Ink Display



Real-time App Notifications



Free Data Storage & Export



Work with Tapo devices



Tapo Hub Required





Tapo Smart Ecosystem

Tapo is the easy way to turn your home into a smart home. With the Tapo Hub as a bridge, Tapo Smart Sensor works with a wide range of Tapo accessories. So you can easily control and monitor your home from anywhere.





E-ink Display, clear and sharp from any angle.

Features a 2.7" E-ink display that reads like real paper. No screen glare and daylight readable with a 180 degree viewing angle.



Comparison between an E-ink display and a backlit display.



Highlight

Ptp-link tapo





Smart Plug

Automate Your Appliances

Monitor and adjust your home's comfort level along with other Tapo devices.

For example, turn on a heater connected to Tapo smart plug automatically when the temperature in your home drops too low. Then switch it off when it's warm enough to save energy. Also works on appliances like fans, humidifiers and dehumidifiers.



Get Instant Alerts

Send you instant app notifications when the temperature or humidity levels fall outside your preset ranges.

Perfect for monitoring your green house, cigar humidors, wine cellars, instrument cases and more.



Features

- **High-Accuracy Sensor** Features the Swiss-made sensor chip with real-time data updating every 2s.
- **2.7" E-Ink Display** No screen glare and readable in bright sunlight with a 180° veiwing angle.
- Real-Time Notifications Send you notifications via Tapo app whenever temperature or humidity levels fall outside customized ranges.
- **Smart Actions Support** Connect the actions with other smart devices for home automation.
- **Data Storage & Export** Up to 2 years' free cloud data storage, and export at any time.
- **Comfort Level Indicator** Keep an eye on your home's levels at a glance. Customize your comfort zones in the Tapo app.
- **Switchable Dispaly Unit** One press to switch the temperature unit.

- 2 Year+ Battery Life Battery-powered design and lasts for up to two years with 2 AAA batteries.⁴
- **Easy Installation** Place it anywhere with multiple installation options.
- **Device Sharing** Easily share management permissions with each member of your family.
- **Easy Setup and Use** Set up quickly and easily through the free Tapo app.



Specifications

General

- Wireless: 868 MHz (EU version)¹; 922 MHz (US version)²
- Temperature Range: 0~50°C (32~122°F)³
- Humidity Range: 0%~99%RH
- Temperature Accuracy: ±0.3°C /±0.54°F; (Up to ±0.2°C/ ±0.32°F from 5°C - 60°C / 41°F - 140°F)
- Humidity Accuracy: ±3%RH;
 (Up to ±2%RH from 20%RH 80%RH @ 25°C / 77°F)
- · Refresh Rate: 2 Seconds
- · Battery Life: 2 Years⁴



*Single press the side button to switch the temperature unit °C/ °F. Double press the side buton to switch display position of temperature and humidity.

Others

- · Package Contents:
 - Smart Monitor Tapo T3153M AdhesiveQuick Start GuideAAA Batteries × 2
- Certifications: FCC, CE, R-NZ, UKCA, RoHS, JRF, VCCI, NCC, RCM
- · Operating Temperature: -20~60°C (-4~140°F)³
- Operating Humidity: 0%–99% RH
- · Dimensions: 62 × 62 × 24.5 mm

Note: Tapo Hub Required

¹ The specific working frequencies for EU version are 863 MHz to 865 MHz and 868 MHz to 868.6 MHz.

³ The screen only displays temperature from 0 to 50°C (32 to 122 °F). If the readings go outside the range, please check the temperature in the Tapo app.

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. ©2022 TP-Link

² The specific working frequencies for US version are 920.9 MHz to 923.3 MHz.

⁴ Battery life estimates obtained through testing in a laboratory setting. Actual result may vary.