

DS-3E0105D-O 5-Port Fast Ethernet Plastic Switch



- 5 x 10/100 Mbps ethernet port
- Supports ADI/ADIX
- Store-and-forward switching
- Supports MAC address auto-learning and aging
- Simple, compact body design
- Supports desktop and wall-mounting installation
- Plug & play, easy to use



Specification

General		
Shell	ABS	
Net Weight	0.093 kg (0.205 lb)	
Dimensions (W × H × D)	83.00 mm × 22.00 mm × 52.00 mm (3.27" × 0.87" × 2.05")	
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)	
Storage Temperature	–40 °C to 85 °C (–40 °F to 185 °F)	
Operating Humidity	5% to 95% (no condensation)	
Relative Humidity	5% to 95% (no condensation)	
Power Supply	5 V DC, 0.6 A	
Installation Mode	Desk-Mounted	
Max. Power Consumption	3 W	
Surge Protection	2 kV	
Network Parameters		
Ports	5 × 10/100 Mbps RJ45 port	
MAC Address Table	2 K	
Switching Capacity	1 Gbps	
Packet Forwarding Rate	0.74 Mpps	
Internal Cache	768Kbits	
Approval		
	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1:	
EMC	2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue	
	7:2020)	
Safety	CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN	
Juicty	62368-1: 2014+A11: 2017)	
Chemistry	CE-RoHS (2011/65/EU),WEEE (2012/19/EU),Reach (Regulation (EC) No.1907/2006)	

Available Model

DS-3E0105D-O

Typical Application





Physical Interface



No.	Indicator/Port	Description
1	100 Mbps RJ45 Port	Used for connection to another device via a network cable.
2	LINK/ACT Indicator	Indicates the statuses of 100 Mbps RJ45 ports 1 to 5.
3	PWR Indicator	Indicates the power status of the switch.
4	Power Supply	Use the attached power adapter to connect the switch to a socket.



Dimension







© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.