

TwistPort™ Adaptor for ePMP-B-6

INTEGRATES EPMP CONNECTORIZED RADIOS
INTO TWISTPORT™ ECO-SYSTEM

The TwistPort™ Adaptor TPA-ePMP-B-6 makes the ePMP™ 4600L and ePMP™ 4600C radio compatible with TwistPort™ Antennas that support 6 GHz band. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the radios with the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick-Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	UV Resistant ABS plastic, Aluminium Alloy
Flame Rating	UL 94 HB
Environmental	IP65
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h (100 mi/h)
Weight	0.45 kg / 1.0 lbs – single unit 0.55 kg / 1.2 lbs – single unit incl. package 12.0 kg / 26.4 lbs – wholesale box (20 units)
Dimensions	Single unit retail box: 157 x 171 x 128 mm (6.2 x 6.7 x 5.0 inch) Wholesale box (20 units): 273 x 330 x 872 mm (10.7 x 13.0 x 34.3 inch)

PERFORMANCE

Frequency Range	5700 - 7125 MHz Check our online SpecCheck for performance data of the particular combination of feed (TPA) and antenna
Polarization	Dual Linear H + V
VSWR	Check our online SpecCheck for performance data of the particular combination of feed (TPA) and antenna
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any WB antenna: SH30WB, SH60WB, SH90WB, AH60WB, AH90WB, UD29WB 5 GHz Antennas: UH-TP-5-24, HG3-TP-S30, UD-TP-21, UD-TP-24, UD-TP-27
Cambium Networks™	ePMP 4600L, ePMP 4600C

PRODUCT DIMENSIONS

