

DS-K1T809EWX
Value Card Terminal

- Slim and flexible design with metal
- Max. 5000 cards and 1000 users.
- Built-in card reader for EM card carding.
- Outdoor application, supports IP65.
- Supports multiple authentication types: card, PIN.
- Supports AP mode and operation via mobile Web


▪ Specification

System	
ROM	16 MB
RAM	448 K
Processor	GD32W515PIQ6
Network	
Wi-Fi	Support
Interface	
Lock control	1
Exit button	1
Door contact input	1
Wiegand	Wiegand out, supports Wiegand 26/34
Capacity	
User capacity	1000
Card capacity	5000
Authentication	
Card type	EM card
Card reading distance	3 cm
Card reading duration	1 s
General	
Button	Physical buttons
Indicator	Support
Power supply	12 VDC, 1 A
Working temperature	-40 °C to 65 °C (-40 °F to 149 °F)
Working humidity	0 % to 90 % (no condensing)
Protective level	IP 65
Dimensions	151 mm × 48 mm × 21.5 mm (5.9" × 1.9" × 0.8")
Weight	Net weight: 220.3 g (0.5 lb) Rough weight: 352 g (0.8 lb)

▪ Available Model

DS-K1T809EWX

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

